


- Vertical Mounting
- Optional Ral Color Selection
- Max Operational Pressure: 6 Bar
- Inlet/Outlet: 1/2" Female Pipe Thread
- All Dimensions are in mm

## SUPPLIED INSTALLATION ACCESSORIES



Product Name	Product Code	Height	Width	Thickness	Plumbing Axes Center to Center	Hanger Axes Horizontal	Hanger to Bottom of the Product	Hanger Axes Vertical	Water Volume	Empty Weight	Thermal Output
		H	W	D	C	S	F	G	-	-	Watt - BTU/hr (Δ50°)
		mm	mm	mm	mm	mm	mm	mm	L	kg	
FONDI 500 X 855	RND-FND085050	855	500	15	50	334	583	374	-	10.8	386 - 1317
FONDI 600 X 855	RND-FND085060	855	600	15	50	434	583	374	-	12.4	445 - 1518
FONDI 500 X 1229	RND-FND122050	1229	500	15	50	334	957	748	-	15.2	549 - 1873
FONDI 600 X 1229	RND-FND122060	1229	600	15	50	434	957	748	-	17.4	630 - 2150
FONDI 500 X 1790	RND-FND179050	1790	500	15	50	334	1518	1309	-	21.8	792 - 2702
FONDI 600 X 1790	RND-FND179060	1790	600	15	50	434	1518	1309	-	25	908 - 3098

