


# HELIN



TOP VIEW

## SUPPLIED INSTALLATION ACCESSORIES



ALLEN KEY 1PCS



SMALL SCREW 4PCS



WALL PLUG 4PCS



SCREW 4PCS



AIR VENT 1PCS




BUCKET 4PCS



WALL BUCKET 4PCS

- Vertical Mounting
- Optional 304 QUALITY STAINLESS STEEL RADIATOR (RNS-HLN5112P:HELIN RADIATOR)
- POLISHED
- MAX Operational Pressure:10Bar
- Inlet/Outlet:1/2"Female Pipe Thread
- All Dimensions are in mm



Product Name	Product Cude	Height	Width	Thick Ness	Plumbing Axes Center to Center	Hanger Axes Horizontal	Hanger To Bottom of the Product	Hanger Axes Vertical	Water Volume	Empty Weight	Thermal Output
		H	W	D	C	S	F	G	-	-	Wat-Btu/hr( $\Delta 50^\circ$ )
		mm	mm	mm	mm	mm	mm	mm	mm	L	kg
RNS-HLN5080P	HELIN 500/10(2+3+5)	826	500	58	460	460	737.5	649	5.4	9.2	375-1279
RNS-HLN5112P	HELIN 500/15(3+5+7)	1121	500	58	460	460	1032.5	944	8.1	12.7	550-1876
RNS-HLN5153P	HELIN 500/20(3+4+5+8)	1534	500	58	460	460	1445.5	1357	10.8	17.9	737-2515

www.reinadesign.co.uk

info@atayglobal.com

TEL:+44 1787 238540

# REINA